

**CERTIFICATE OF ANALYSIS  
 CONTOSOL PAINTPRO**

TEST DESCRIPTION	METHOD	SPECIFICATION	RESULT
Appearance	*ASTM D4176	Bright and Clear	Bright & clear
COLOUR (saybolt)	*ASTM D156	Min. +30	30
Flash Point (open cup ) °C	*ASTM D93	50 Min	51
Density g/ml @ 30°C		0.810,-0.830	0.820
Pour Point °C			+10
Smell		Strong sweet	Strong sweet

**APPLICATION:-**  
**FOR INDUSTRIAL USE ONLY**  
 Paint additive  
 Rust Preventive Solvent base  
 Other Industrial uses

**Note :** \* Refer the Safety Data Sheet for safety & handling guidelines for this product.  
 ➤ It is the responsibility of the user to ensure that the products are used in the applications for which they are intended and comply with all applicable laws & regulations.

WWW.CONTOL.IN

**CONTINENTAL PETROLEUMS LTD.**

- The above data is indicative of recent average values minor variations which do not affect product performance or quality.
- The figures quoted are typical, do not constitute a specification and are subject to the usual manufacturing tolerances.

 Enquiry # Email Id: [conpetco@gmail.com](mailto:conpetco@gmail.com) Phone: 0141-222 22 32

January 2021