

## CERTIFICATE OF ANALYSIS

# CONTSOL 120 (DA)

**CONTSOL 120 (DA) is a low Aromatic hydrocarbon solvent used in various applications. This fluid is produced from carefully selected feed stocks and is free of chlorinated and glycol ether components.**

**CONTSOL 120 (DA)**

TEST	TEST METHOD	UNIT	SPEC LIMITS	RESULTS
Apperance	Visual		C & B and free From Sediments	Clear
IBP	ASTM D 86	°C	250 MIN	267
FBP			310 MAX	306.0
Density @ 15 Deg C	ASTM D 4052	Kg/m3	0.81-0.84	0.8289
Flash Point	ASTM D93	°C	115 MIN	116
Sulfur Content	ASTM D 5453	PPM	5 MAX	<1.0
Aromatics	UOP 495/UV Internal Method	% Vol	0.05 MAX	ND
Saybolt Color	ASTM D 156		+30 MIN	.30
Pour Point	ASTM D 97	°C	-35 MIN	-38
Kinematic Viscosity 40 °		CST	4 MIN	3.763

### **FOR INDUSTRIAL APPLICATION ONLY**

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>➤ Dry Cleaning Solvent</li> <li>➤ Metal Cleaning Solvent</li> <li>➤ Low Odor Paint Solvent</li> <li>➤ Metal Working Oil Base</li> <li>➤ Cutting Oil Base</li> <li>➤ Aluminum Rolling Oil Base</li> <li>➤ Anti -rusting Oil Base</li> <li>➤ Underbody Wax Base Oil</li> <li>➤ Dewaxing Solvent</li> <li>➤ Plasticizer Diluents</li> </ul> | <ul style="list-style-type: none"> <li>➤ Insects Aerosol Solvent</li> <li>➤ Insects Liquid Fumigator</li> <li>➤ Silicone Sealant Oil</li> <li>➤ Drilling Oil</li> <li>➤ Explosive Lubricating Oil</li> <li>➤ Printing Ink Solvent</li> <li>➤ Candle Oil</li> <li>➤ Flocculant Solvent</li> <li>➤ EDM Oil</li> <li>➤ Textile Oil Base</li> </ul> |
|---|---|

**Note : \*** Refer the Safety Data Sheet for safety & handling guidelines for this product.

- It is the responsibility of the user to ensure that the products are used in the applications for which they are intended and comply with all applicable laws & regulations.

## **CONTINENTAL PETROLEUMS LTD.**

- The above data is indicative of recent average values minor variations which do not affect product performance or quality.
- The figures quoted are typical, do not constitute a specification and are subject to the usual manufacturing tolerances.