

Continental Petroleums Ltd.

email : conpetco@gmail.com

CONTOL Super 40, 50

Product Description

Contol Super 40, 50 is a monograde diesel engine oil for automotive and industrial applications. They are formulated with high quality base stocks and contain a balanced additive system, to provide highly effective controls over wear and deposits.

Features Advantages and Potential Benefits

- A low ash product suitable for diesel engines.
- Protection against mechanical wears and deposits.
- Extends overhaul intervals.
- Suitable for mixed fleet intervals.

Cont. on Page 2

Applications

Contol Super 40, 50 is monograde engine oil suitable for automotive as well as stationary engines. It can also be used for some types of gasoline engines, making it ideal for mixed fleet operations. It has the long drain oil characterstic and maintains performance features throughout its service life.

Specifications

API CF Performance levels.

Pack Sizes : 210 L, 50 L, 5 L, 4 L, 3.5 L, 1 L

Typical Properties

SAE Grade	40	50
Viscosity, ASTM D445		
cSt @40 Deg.C	148.0	196.0
cSt @100 Deg.C	15.6	18.5
Viscosity Index, ASTM D 2270	103	102
Pour Point, Deg.C, ASTM D 97	-18	-18
Flash Point, Deg.C, ASTM D 92	240	240
Base Number mg KOH/g	7.5	7.5
Specific Gravity @15Deg.C, ASTM D 4052	0.902	0.905
Color, ASTM D-1500	3.0	3.5
Sulphated Ash, % wt. ASTM D-874	0.821	0.821