

Continental Petroleums Ltd.

email : conpetco@gmail.com

CONTOL Super Brake Fluids

Product Description

Contol Super Brake Fluids Series is formulated as non-petroleum chemical fluids for use in the hydraulic brake and clutch systems of automotive vehicles. They offer protection against corrosion and rusting of metal parts, even in the presence of moisture. They possess high boiling points and low pour points. They do not affect natural or synthetic rubber washers.

Features Advantages and Potential Benefits

- Compatible with other brands meeting similar specifications.
- Good protection against corrosion & rust.

Applications

Contol Super Brake Fluids Series is suitable for all hydraulic brake and clutch, disc and drum systems where such type of fluid is specified. They do not affect natural or synthetic rubber seal materials generally used.

Specifications

DOT 3.....SAE J1703F
.....FMVSS No. 116/DOT3

DOT 4.....SAE J1703F
.....FMVS No. 116/DOT4

Pack Sizes : 250 ml, 500 ml, 100 ml

Cont. on Page 2

Continental Petroleum Ltd.

email : conpetco@gmail.com

--2--

Typical Properties

Performance	DOT 3	DOT 4
Viscosity, ASTM D445		
cSt @-40 Deg.C, mm ² /s	<1500	<1800
cSt @100 Deg.C, mm ² /s	>1.5	>1.5
Equilibrium Reflux Boiling Point, Min., Deg.C	205	230
Rubber Swelling Test	Pass	Pass
Resistance to Oxidation	Pass	Pass
Density at 20 Deg.C, g/ml, ASTM D-4052	1.03	1.07